EXPERIENCE SOUND

MX-20
MODULAR SPEAKER SYSTEM

Designed for dedicated home cinemas with an acoustically transparent screen

Minimum screen size 16:9 105" (2324 x 1308mm)
Minimum screen size 21:9 130" (3035 x 1301mm)



	MX-20 LCR
Frequency Range	40 Hz - 20 kHz
Power Handling	100 - 500 Watts RMS recommended amplifier power
Sensitivity	97 dB (2.83V / 1m)
Impedance	8 Ohms
Configuration	2-Way
Low Frequency Driver	Single 255mm (10") paper cone driver. 50mm (2") voice coil wound on high powered kapton former, with ventilated magnet assembly and copper shorting ring for low distortion
High Frequency Driver	26mm (1") doped fabric dome with large roll surround. Ferro fluid cooled. Coupled to a Krix designed 90 x 40 short throw waveguide
Weight	31kg each

	MX-20 Subwoofer
Frequency Range	25 Hz - 200 Hz
Power Handling	200 - 1400 Watts RMS recommended amplifier power
Sensitivity	96 dB (2.83V / 1m)
Impedance	8 Ohms
Configuration	Bass reflex, down firing vent
Low Frequency Driver	Single 380mm (15") paper cone driver with 100mm (4") edge-wound copper voice coil, dual spider assembly and vented magnet assembly
Weight	45kg each

ADELAIDE | 14 Chapman Road, Hackham, SA, 5163, Australia T +61 8 8384 3433 F +61 8 8384 3419 listen@krix.com.au